

SuperServer 4029GP-TRT



Integrated Board



X11DPG-OT-CPU



X9DRG-O-PCIE

Views: | [Angled View](#) | [Top View](#) | [Front View](#) | [Rear View](#) |

► [Drivers & Utilities](#) ► [BIOS](#) ► [IPMI](#) ► [Tested Memory](#) ► [Tested M.2 List](#) ► [NVMe Options](#) ► [Manuals](#) ► [OS Certification Matrix](#) ► [Compatible GPU List](#) ► [Drive Options](#) ► [4U PCIe Root Architectures](#)

Key Features

- 3D Rendering
- Astrophysics, Chemistry
- Cloud and Virtualization needs
- Cloud Computing
- Compute Intensive Application
- Dual Root System for balanced performance & higher CPU to GPU communication

1. Dual Socket P (LGA 3647) support 2nd Gen Intel® Xeon® Scalable processors (Cascade Lake/Skylake)[‡]
2. 24 DIMMs; up to 6TB 3DS ECC DDR4-2933MHz[†] RDIMM/LRDIMM, Supports Intel® Optane™ DCPMM^{††}
3. 8 PCI-E 3.0 x16 slots (support up to 8 double width GPU), 2 PCI-E 3.0 x8, 1 PCI-E 3.0 x4
4. Up to 24 Hot-swap 2.5" drive bays; 8x 2.5" SATA drives supported with included H/W, 2x 2.5" NVMe drives supported with included H/W, 1 NVMe based M.2 SSD
5. 2x 10GBase-T LAN ports via Intel C622
6. 8 Hot-swap 92mm RPM cooling fans
7. 2000W (2+2) Redundant Power Supplies **Titanium Level (96%+)**

Note: Image above may show a varied configuration of optional parts. Please refer to parts list for standard parts included.

Specifications

Product SKUs

SYS-4029GP-TRT	SuperServer 4029GP-TRT (Black)
-----------------------	---

Motherboard

Super X11DPG-OT-CPU

Processor/Cache

CPU	- Dual Socket P (LGA 3647) 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors[†], 3 UPI up to 10.4GT/s - Support CPU TDP 70-205W
Cores	Up to 28 Cores
Note	[†] BIOS version 3.2 or above is required to support 2nd Gen Intel® Xeon® Scalable processors (codenamed Cascade Lake-R)
GPU Support	Please refer to: Compatible GPU list

System Memory

Memory Capacity	24 DIMM slots - Up to 6TB 3DS ECC DDR4-2933MHz[†] RDIMM/LRDIMM - Supports Intel® Optane™ DCPMM^{††}
Memory Type	2933[†]/2666/2400/2133MHz ECC DDR4 RDIMM/LRDIMM
Note	[†] 2933MHz in two DIMMs per channel can be achieved by using memory purchased from Supermicro ^{††} Cascade Lake only. Contact your Supermicro sales rep for more info.

On-Board Devices

Chipset	Intel® C622 chipset
SATA	SATA3 (6Gbps) with RAID 0, 1, 5, 10
Network Controllers	Dual Port 10GbE from C622
IPMI	- Support for Intelligent Platform Management Interface v.2.0 - IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
Graphics	ASPEED AST2500 BMC

Input / Output

SATA	10 SATA3 (6Gbps) ports
LAN	2 RJ45 10GBase-T LAN ports 1 RJ45 Dedicated IPMI LAN port
USB	4 USB 3.0 ports (rear)
Video	1 VGA Connector

Chassis

Form Factor	4U Rackmountable - Rackmount Kit (MCP-290-00057-0N)
Model	CSE-418GTS-R4000BP2

Dimensions

Height	7.0" (178mm)
Width	17.2" (437mm)
Depth	29" (737mm)
Weight	- Net Weight: 65.5 lbs (29.7 kg) - Gross Weight: 100 lbs (45.3 kg)
Available Colors	Black

Drive Bays / Storage

Hot-swap	- Up to 24x 2.5" SAS/SATA drive bays 8x 2.5" SATA supported natively 2x 2.5" NVMe supported natively
M.2	1 NVMe based M.2 SSD - Form Factors: 2260, 2280, 22110

Expansion Slots

PCI-Express	8 PCI-E 3.0 x16 (double-width) slots 2 PCI-E 3.0 x8 slots 1 PCI-E 3.0 x4 slot
--------------------	---

System Cooling

Fans	8 Hot-swap 92mm cooling fans
-------------	--

Power Supply

2000W Redundant Power Supplies with PMBus

Total Output Power	1000W: 100 – 120Vac 1800W: 200 – 220Vac 1980W: 220 – 230Vac 2000W: 230 – 240Vac 2000W: 200 – 240Vac (UL/CUL only)
Dimension (W x H x L)	73.5 x 40 x 265 mm
Input	100-120Vac / 12.5-9.5A / 50-60Hz 200-220Vac / 10-9.5A / 50-60Hz 220-230Vac / 10-9.8A / 50-60Hz 230-240Vac / 10-9.8A / 50-60Hz 200-240Vac / 11.8-9.8A / 50-60Hz (UL/cUL only)
+12V	- Max: 83.3A / Min: 0A (100-120Vac) - Max: 150A / Min: 0A (200-220Vac) - Max: 165A / Min: 0A (220-230Vac) - Max: 166.7A / Min: 0A (230-240Vac) - Max: 166.7A / Min: 0A (200-240Vac) (UL/cUL only)
12Vsb	Max: 2.1A / Min: 0A
Output Type	25 Pairs Gold Finger Connector

COM Port	■ 1 COM port (header)
----------	-----------------------

System BIOS

BIOS Type	■ AMI 32Mb SPI Flash ROM
-----------	--------------------------

Management

Software	■ Intel® Node Manager ■ IPMI 2.0 ■ KVM with dedicated LAN ■ SSM, SPM, SUM ■ SuperDoctor® 5 ■ Watchdog
----------	---

PC Health Monitoring

CPU	■ Monitors for CPU Cores, Chipset Voltages, Memory. ■ 4+1 Phase-switching voltage regulator
FAN	■ Fans with tachometer monitoring ■ Status monitor for speed control ■ Pulse Width Modulated (PWM) fan connectors
Temperature	■ Monitoring for CPU and chassis environment ■ Thermal Control for fan connectors

Certification	 	Titanium Level [Test Report]
---------------	---	---

Operating Environment

RoHS	■ RoHS Compliant
Environmental Spec.	■ Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) ■ Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) ■ Operating Relative Humidity: 8% to 90% (non-condensing) ■ Non-operating Relative Humidity: 5% to 95% (non-condensing)

Parts List

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X11DPG-OT-CPU	1	Super X11DPG-OT-CPU Motherboard
	MBD-X9DRG-O-PCIE	1	Super X9DRG-O-PCIE Motherboard
	CSE-418GTS-R4000BP2	1	CSE-418GTS-R4000BP2 Chassis
Backplane	BPN-SAS3-216A-N4	1	24-port 2U SAS3 12Gbps hybrid backplane, support up to 20x 2.5-inch SAS3/SATA3 HDD/SSD and 4x SAS3/SATA3/NVMe Storage Devices
Cable 1	CBL-0449L	2	HDD power extension for X8OBN, special 8 pin to 4 HDD. 45cm. 18AWG
Cable 2	CBL-PWEX-1028	8	GPU,2x4F/CPU to 2x4F/CPU,P4.2, 30CM,16AWG, 10A/pin, -40~105C
Cable 3	CBL-SAST-0507-01	2	MINI SAS HD-MINI SAS,6G,INT,80CM,SB,28AWG
Cable 4	CBL-SAST-0972	2	OcuLink V. 1.0 source to MiniSAS HD,INT,PCIe, 70CM,34AWG,RoH
Parts	MCP-130-41801-0B	1	Black plastic palm cover for X9DRG-O-PCIE
Riser Card	RSC-X9DRG-O	4	RSC-X9DRG-O
Heatsink / Retention	SNK-P0068APS4	2	2U Active CPU Heat Sink Supporting Narrow Bolster Plate Mounting Mechanism for X11 Purley Platform
Power Supply	PWS-2K05A-1R	4	1U 2000W Redundant Titanium Power Supply W/PMbus 73.5x40x265mm,RoHS/REACH
FAN 1	FAN-0151L4	8	92x92x38 mm, 11.5K RPM, SC418G Middle Fan w/ Housing,RoHS/REACH,PBF
Rear Window	MCP-240-84802-0N	1	21 slot rear window for SC418X

Optional Parts List

	Part Number	Qty	Description
0.5U LID	MCP-230-41803-0N	1	Top cover for GTX card support
1U LID	MCP-230-41806-0N	1	Top cover for NVLINK BRIDGE support
2.5" NVMe Drive Trays	MCP-220-00121-0B	1 per drive	Black Gen-3 2.5" NVMe drive tray. Orange tab with lock
	MCP-220-00167-0B		Black Gen-3 2.5" NVMe drive tray. Orange tab with lock, Tool-less
GPU Dummy Tray	MCP-240-00096-0N	1	GPU / Add-on Card Dummy Assembly (2 Slots)
GPU Cables	CBL-PWEX-0665	1 per GPU	GPU power cable (for NVIDIA P40, M40, M60, AMD MI25). 8pin FEMALE BLK to 8pin FEMALE WHT. 30cm 18AWG.
	CBL-PWEX-1017	1 per GPU	GPU power cable (for NVIDIA QUADRO, GTX). 8pin FEMALE CPU BLUE to 2x 6pin FEMALE / 2x 1pin FEMALE. 20cm 16AWG/20AWG.
	CBL-PWEX-1040 ¹	1 per GPU	GPU power cable (for NVIDIA QUADRO, GTX). 8pin MALE CPU to 2x 6pin FEMALE / 2x 1pin FEMALE. 5cm 20AWG/16AWG.
	CBL-PWEX-1028 ⁹	1 per GPU	GPU power cable (for NVIDIA TESLA V100). 8pin FEMALE CPU BLUE to 8pin FEMALE CPU BLUE. 30cm 20AWG/16AWG.
Note:	1. Use with CBL-PWEX-1028 9. 8 qty. included with each system		
Storage Control Cards and Cables	AOC-S3008L-L8I ²	1	Broadcom 3008 STD LP 8 internal ports, 12Gb/s per port - SAS HBA Adapter Card, RAID 0,1,1E,10
	AOC-S3008L-L8E ²	1	Broadcom 3008 STD LP 8 internal ports, 12Gb/s per port - SAS HBA Adapter Card, HBA only
	AOC-S3108-H8IR ^{2, 4, 8}	1	Broadcom 3108 STD LP 8 internal ports, 12Gb/s per port - SAS HBA Adapter Card, RAID 0,1,5,6,10,50,60

	AOC-S3108L-H8IR-16DD ^{4, 8}	1	Broadcom 3108 STD LP 8 internal ports, 12Gb/s per port - SAS HBA Adapter Card, RAID 0,1,5,6,10,50,60. Maximum 16 HDD support with expander backplane
	AOC-SAS3-9361-16I ^{3, 5}	1	Broadcom 9361 STD LP 16 internal ports, 12Gb/s per port - SAS HBA Adapter Card, RAID 0,1,5,6,10,50,60.
	AOC-SAS3-9361-24I ^{5, 6}	1	Broadcom 9361 STD LP 24 internal ports, 12Gb/s per port - SAS HBA Adapter Card, RAID 0,1,5,6,10,50,60.
	CBL-SAST-0531	2	n/a
	BTR-TFM4G-LSI00418 ⁷	1	LSI Remote CVKit with DVFlash Module CVFM04 for 9361 and 9380 Controller Series
	BTR-TFM8G-LSICVM02	1	LSI Supercap w/ 8GB CV + 24" cable for LSI S3108-H8IR. Whole kit includes: - MCP-240-00127-0N - BKT-BBU-BRACKET-05
	MCP-240-00127-0N	1	Remote Mounting Bracket for Supercap. Installs in 2.5" drive tray.
	BKT-BBU-BRACKET-05	1	Remote Mounting Board for Supercap. Installs in 2.5" drive tray.
	BPN-SAS3-216EL1	1	SAS3 12Gb/s Single Expander Backplane with x24 2.5" SATA/SAS HDD/SSD.
Note:	2. Requires x2 CBL-SAST-0531 3. Requires x4 CBL-SAST-0531 4. Use BTR-TFM8G-LSICVM02 for Supercap 5. Use BTR-TFM4G-LSI00418 for Cache Vault 6. Requires x6 CBL-SAST-0531 7. Requires BKT-BBU-BRACKET-05 8. Optional BPN-SAS3-216EL1 Expander Backplane support. Will lose x2 U.2 NVMe support		
Network and Cables	AOC-STG-i4S	1	4 Port 10G SFP+ PCI-E x8 Ethernet card. Based on Intel X710-AMI
	AOC-STG-i2T	1	2 Port 10G RJ45 PCI-E x8 Ethernet card. Based on Intel X540
	AOC-S25G-B2S	1	2 Port 25G SFP28 PCI-E x8 Ethernet card. Based on Broadcom BCM57414
	AOC-S25G-M2S	1	2 Port 25G SFP28 PCI-E x8 Ethernet card. Based on Mellanox ConnectX-4 LX EN
	AOC-MCX4121A-ACAT	1	2 Port 25G SFP28 PCI-E X8 Ethernet card. Based on Mellanox ConnectX-4 LX EN
	AOC-S40G-I1Q	1	1 Port 40G QSFP+ PCI-E X8 Ethernet card. Based on Intel X710
	AOC-S40G-I2Q	1	2 Port 40G QSFP+ PCI-E X8 Ethernet card. Based on Intel X710
	AOC-MCX456A-ECAT	1	2 Port 100G QSFP28 PCI-E X16 EDR IB card. Based on Mellanox Connect-4 VPI
	AOC-MCX556A-ECAT	1	2 Port 100G QSFP28 PCI-E X16 EDR IB card. Based on Mellanox Connect-5 VPI
	CBL-NTWK-0944-MS28C30M	1	Ethernet Cable, SFP28,28GbE,PASSIVE,30 AWG,3M,Mellanox
	CBL-NTWK-0944-MS28C20M	1	Ethernet Cable, SFP28,28GbE,PASSIVE,30 AWG,2M,Mellanox
	AOC-E10GSFPSR	1	Ethernet Transceiver, SFP+ 1000Base-SX / 10GBase-SR
	CBL-NTWK-0446-01	1	Ethernet Cable, QSFP, 40GbE, PASSIVE, 28 AWG, 3M
	CBL-NTWK-0942-MQ28E20M	1	IB Cable, QSFP28, 100GbE, PASSIVE, 28 AWG, 2M
Global Services & Support	<u>QS4HR3/2/1</u>	-	3/2/1-year onsite 24x7x4 service
	<u>QSNBD3/2/1</u>	-	3/2/1-year onsite NBD service
Software	<u>SFT-OOB-LIC</u> • <u>eStore</u>	1	OOB Management Package (per node license)
Software	<u>SFT-DCMS-Single</u>	1	DataCenter Management Package (per node license)

